

Section 1: IDENTIFICATION**Product Name:** Eco Touch Paint Polish + Wax**Additional Names:****Manufacturer's Part Number:** PPS16, PPS1G, PPS5G, PPS55G**Recommended Use:** Paint polish and wax**Company:** Eco Touch, Inc.

One Washington St. Suite 200

Dover, NH 03820

Telephone: 888.375.7970 • 603.305.5747 *Mon – Fri, 9am – 5pm EST***Fax:** 603.319.1257**Email:** info@ecotouch.net**Emergency Phone:** Medical/Poison Control 24 Hour: 800.222.1222**Section 2: HAZARDS IDENTIFICATION**

The label elements below were prepared in accordance with OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Classification of the substance or mixture

The product is not classified as hazardous under OSHA Hazard Communication Standard, 29 CFR 1910.1200.

OSHA HCS 2012Label Elements**Signal Word:** None**Hazard Symbol(s)/Pictogram(s):****Hazard Statements:****Precautionary Statements:**

P264 – Wash hands thoroughly after handling.

P270 – Do not eat, drink or smoke when using this product

P501 – Dispose of contents/container in accordance with local, regional and national regulations.

Hazards Not Otherwise Classified (HNOC): None**Other Information:** None Known**Section 3: COMPOSITION/INFORMATION ON INGREDIENTS**

<u>Ingredient</u>	<u>CAS Number</u>	<u>Percent Range</u>
Aqua (water)	7732-18-5	80 – 100%*
Hydrotreated Light Petroleum Distillates	64742-47-8	1 – 10%*
Aluminum Oxide	1344-28-1	1 – 10%*
Polydimethylsiloxane	63148-62-9	0.5 – 5.0%*
Carnauba Wax	8015-86-9	0.5 – 5.0%*
White Mineral Oil	8042-47-5	0.30 – 3.0%*
Alcohol Ethoxylates	68439-46-3	0.30 – 3.0%*
Sodium Carbonate	497-19-8	0.01 – 0.10%*
5, 5-Dimethylhydantoin Preservative	77-71-4	0.01 – 0.10%*

* The specific chemical identity and/or exact percentage of this composition has been withheld as a trade secret

Section 4: FIRST-AID MEASURES

Inhalation: Not expected to cause respiratory irritation. If adverse effect occurs, move to fresh air.

Skin Contact: Not expected to cause skin irritation. If adverse effect occurs, rinse skin with water.

Eye Contact: Not expected to cause eye irritation. If adverse effect occurs, flush eyes with water.

Ingestion: May cause upset stomach. Drink plenty of water to dilute.

Most Important Symptoms/Effects, Acute and Delayed: Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Indication of Immediate Medical Attention and Special Treatment Needed, if necessary: Treat symptomatically

Section 5: FIRE-FIGHTING MEASURES

Suitable & Unsuitable Extinguishing Media: Dry chemical foam, carbon dioxide.

Specific Hazards Arising from Chemical: Hazardous decomposition: Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Formaldehyde, Oxides of Nitrogen, Oxides of Carbon, Silicone Dioxide, Hydrocarbons.

Special Protective Actions for Fire-Fighters: Must wear NIOSH/MSHA approved self-containing breathing apparatus and protective clothing. Cool fire-exposed containers with water spray.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures: *For non-emergency and emergency personnel:* See section 8 – personal protection. Avoid eye contact. Safety goggles required.

Environmental Precautions: Do not allow into open waterways and ground water systems.

Methods and Materials for Containment and Clean Up: Isolate spill or leak area immediately. Keep unauthorized personnel away. Stay upwind. Keep out of low area. Ventilate closed spaces before entering. Do not touch or walk through spilled material. Wear appropriate protective equipment during cleanup. Small spills: Absorb with earth, sand, or other non-combustible material and transfer to containers for later disposal. Large spills: Dike ahead of liquid spill for later disposal. Prevent entry into waterways, sewers, basements or confined areas. Surfaces may become slippery after slippage.

This product is non-flammable. See Section 9 for Physical Properties.

Section 7: HANDLING AND STORAGE

Precautions for Safe Handling: Ensure adequate ventilation. Keep out of reach of children. Keep away from heat, sparks, open flame and direct sunlight. Do not pierce any part of the container. Do not mix or contaminate with any other chemical. Do not eat, drink or smoke while using this product.

Conditions for Safe Storage including Incompatibilities: Keep container tightly closed. Keep in cool dry area. Avoid prolonged exposure to sunlight. Do not store at temperatures above 109°F (42.7°C). Store in original container in areas inaccessible to children. Do not store on side. Offer for recycling if available or discard in trash. Do not expose to chlorine bleach.

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION**Exposure Limit Values:**

Ingredient	CAS Number	Agency	Limit Type	Additional Comments
Hydrotreated Light Petroleum Distillates	64742-47-8	OSHA	TWA 165 ppm	
Aluminum Oxide	1344-28-1	OSHA	TWA (as dust): 15 mg/m ³	
White Mineral Oil	8042-47-5	OSHA	TWA (as dust): 5 mg/m ³	

Appropriate Engineering Controls: Showers, eyewash stations, ventilation systems.

Individual Protection Measures / Personal Protective Equipment (PPE)

Eye Contact: Use protective glasses or safety goggles if splashing or spray-back is likely

Respiratory: Use in well ventilated areas or local exhaust ventilations when cleaning small spaces.

Skin Contact: Use protective gloves

General Hygiene Considerations: Wash thoroughly after handling and before eating or drinking.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Viscous Tan Liquid	Partition Coefficient: n-octanol/water:	Not determined
Odor:	Characteristic	Autoignition Temperature:	Non-flammable
Odor Threshold:	Not determined	Decomposition Temperature:	Not determined
pH:	8.0 – 9.0	Viscosity:	Thick
Freezing Point:	0°C (32°F)	Specific Gravity:	0.98 g/ml
Boiling Point & Range:	100°C (212°F)	VOCs:	0% (LVP Exempt Solvent 0.03 mm Hg) at 20°C
Flash Point:	> 200°F	VOC Composite Partial Pressure:	Not determined
Evaporation Rate:	Not determined	Relative Density:	8.17 – 8.345 lb/gal
Flammability (solid, gas):	Not determined	Solubility:	Partially soluble
Upper/Lower Flammability:	Not determined		
Vapor Pressure:	Not determined		
Vapor Density:	Not determined		

Section 10: STABILITY AND REACTIVITY

Reactivity:	Non-reactive.
Chemical Stability:	Stable under normal conditions
Possibility of Hazardous Reactions:	Reactive with oxidizers
Conditions to Avoid:	Excessive heat or cold.
Incompatible Materials:	Do not mix with chlorine bleach
Hazardous Decomposition Products:	Thermal decomposition may produce toxic vapors/fumes of oxides of carbon.

Section 11: TOXICOLOGICAL INFORMATION

Likely Routes of Exposure:	Inhalation -	Not expected to cause irritation
	Skin Contact -	Not expected to cause irritation, repeated contact may cause dry skin
	Eye Contact -	Not expected to cause irritation
	Ingestion -	May cause upset stomach

Symptoms related to the physical, chemical and toxicological characteristics: No symptoms expected under typical use conditions.

Delayed and immediate effects and or chronic effects from short term exposure: No health effects information available for human exposure.

Safety Data Sheet: Eco Touch Paint Polish + Wax

Version No. 1

Issue Date: March 3, 2015

Supersedes Date: N/A

*Delayed and immediate effects and or chronic effects from long term exposure: Dry skin or skin irritation may occur.**Interactive effects: Not known.*Numerical Measures of Toxicity

Name	Route	Species	Value (LD50)
Polydimethylsiloxane	Ingestion	Rat	>17,000 mg/kg
Alcohol Ethoxylates	Ingestion	Rat	>2,000 mg/kg
White Mineral Oil	Ingestion	Rat	>5,000 mg/kg
5, 5-Dimethylhydantoin Preservative	Ingestion	Rat	2,890 mg/kg

No toxicity information is available for this specific material. This toxicity information provided is for the individual components.

Skin Corrosion/Irritation:	Mixture does not classify under this category.
Eye Damage/Irritation:	Mixture does not classify under this category.
Germ Cell Mutagenicity:	Mixture does not classify under this category.
Carcinogenicity:	Mixture does not classify under this category.
Reproductive Toxicity:	Mixture does not classify under this category.
STOT-Single Exposure:	Mixture does not classify under this category.
STOT-Repeated Exposure:	Mixture does not classify under this category.
Aspiration Hazard:	Mixture does not classify under this category.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity:	Volume of ingredients used does not trigger toxicity classifications under the Globally Harmonized System of Classification and Labeling of Chemicals.
Aquatic:	Not tested on finished formulation.
Terrestrial:	Not tested on finished formulation.
Persistence and Degradability:	No data available.
Bioaccumulative Potential:	No data available.
Mobility in Soil:	No data available.
Other Adverse Effects:	No data available.

Section 13: DISPOSAL CONSIDERATIONS**Waste treatment methods**

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.

Section 14: TRANSPORT INFORMATION

U.N. Number:	Not applicable	U.N. Proper Shipping Name:	Cleaning Compound, Liquid NOI
Transport Hazard Class(es):	Not applicable	NMFC Number:	48580-3
Packing Group:	Not applicable	Class:	55
Environmental Hazards:	Marine Pollutant - NO	ICAO/ IATA:	Not classified as Hazardous
U.S. (DOT) / Canadian TDG:	Not Regulated for shipping.	ADR/RID:	Not classified as Hazardous
IMO / IDMG:	Not classified as Hazardous		

Transport in Bulk (according to Annex II of MARPOL 73/78 and IBC Code): Unknown.

Safety Data Sheet: **Eco Touch Paint Polish + Wax**

Version No. 1

Issue Date: March 3, 2015

Supersedes Date: N/A

Special precautions which user needs to be aware of/comply with, in connection with transport or conveyance either within or outside their premises None known.

Section 15: REGULATORY INFORMATION

All components are listed on: TSCA and DSL Inventory.

SARA Title III: Sections 311/312 Hazard Categories – Not applicable.
Sections 313 Superfunds Amendments and Reauthorizations Act of 1986 – Not applicable.
Sections 302 – Not applicable.

Clean Air Act (CAA): Not applicable

Clean Water Act (CWA): Not applicable

State Right To Know Lists:

California Proposition 65: No ingredients listed

New Jersey RTK : No ingredients listed

Pennsylvania RTK: No ingredients listed

Section 16: OTHER INFORMATION

Acronyms

NTP	National Toxicology Program	IARC	International Agency for Research on Cancer
OSHA	Occupational Safety and Health Administration	CPSC	Consumer Product Safety Commission
TSCA	Toxic Substances Control Act	DSL	Domestic Substances List

Prepared / Revised By: Eco Touch, Inc.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

DISCLAIMER: The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.